



DigiFort® wall media NW350

Fabric backed non woven commercial wallcovering
product sheet

General description:

Non Woven backed wallcovering suitable for ink jet printing

Roll specifications:

Width: 130 cm.
Length: 50 * lm.
* Other roll lengths available on request
"Internal" core diameter 7,6 cm

Composition:

Substrate weight: 60 ± 20 g/m² EN ISO 2286-2
Vinyl weight 290 ± 20 g/m² EN ISO 2286-2
Total weight 350 ± 20 g/m² EN ISO 2286-2
Thickness * mm EN ISO 2286-3
* Depends on embossing / structure

Printing inks:

Suitable for Solvent, Eco Solvent and UV-curable

Properties:

Coating Specially formulated acrylic laquer with exclusive ink jet properties.

Washability prior to printing:

Scrubbable EN 259 –2

In general; Digitally printed wallcovering can be washed. Slight or moderate soiling can be removed using a combination of mild detergent and a damp cloth. Dabbing – certainly not rubbing is recommended to lift the soil. It is important to rinse off with clean water (absorbant) cloth washing in a low to high vertical action to prevent moisture at skirting level. Bleach, abrasive cleaners and similar compounds must not be used.

Resistance to chemicals prior to printing:

Resistant to: Soap; Detergents; Alcohol; Ammonia; Alkali; Diluted Acids.
Not resistant to: Solvents like Ketones; Esters; Aromatic hydrocarbons.

Installation:

Refer to installation recommendations leaflet inside the core of each roll.

Adhesives:

Heavy duty wallcovering adhesive BK 10 (manual) or BK 23 (industrial), or similar PVA substitute.

Safety/Ecological:

The material is classified as non-hazardous DIN 52900 or 91/155/EEG,2001/58/EC

Fire resistance:

Fire rating

Euro class B s1d0
Class 0 / 1 BS 476 part 6/7
M1 NF P 92501 / 92507
B1 DIN 4102 – 01 *
* ABP Number : P-MPA-E-04-507

Lightfastness:

≥ 7 International Woolscale BS EN 20105 / ISO 105-B02