

Visual Communication - RI-Mark

Issue date : Date last modification :
17/02/2011**06237 ETCH GLASS PTF AIRFLOW MATT CLEAR ASP 26 PERMANENT WKPE 160****Face Material**

Polymeric matt clear frosted vinyl, with good flexibility and conformability to curved surfaces.

Type	Polymeric vinyl		
Colour and Finish	Matt clear frosted		
Weight	110 g/m ² ±10%	ISO 536	
Thickness	80 µ ±10%	ISO 534	

Adhesive

Acrylic permanent solvent based adhesive.

Reference	ASP26 with Air Flow liner		
Type	Acrylic Permanent		
Min. Appl. Temp.	+10°C		
Service Temp.	-20°C / +120°C		
Shear	Medium		
Tack	6 N/inch ²	FINAT FTM9	
Final Adhesion	12 N/inch	FINAT FTM2	

Liner

Type	2 side PE coated 1 side siliconised embossed		
Colour and Finish	White		
Weight	160 g/m ² ±10%	ISO 536	
Thickness	190 µ ±10%	ISO 534	

Applications

For matt clear frost applications. Size available: h 1220 mm X 50 m.

Printing Methods

As a rule it is not printed.

Shelf life

60 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.

