

TECHNICAL DATA SHEET

Digital Carpet Non Woven Type 1

DESCRIPTION:

Digital Carpet Non Woven Type 1 is a non woven printable carpet suitable for UV and dyel sublimation printers. It is best suited for indoor carpet or door mats. Digital Carpet Non Woven type 1 is engineered for indoor use but can be used outdoors for short durations and is ideal for use in corporate lobbies, waiting areas, foyers and trade show booth floor graphics.

PHYSICAL PROPERTIES:

The following information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guaranty and do not constitute a warranty. Therefore, the results obtained from the use thereof, or that any use will not infringe upon any patent. The purchaser should independently determine,

| Characteristics | Test Method | Metric | English |
|-------------------|----------------------|-------------------------|-------------------------|
| Pile | N/A | 100% polyester | 100% polyester |
| Construction | N/A | Non woven with pre-coat | Non woven with pre-coat |
| Total Height | N/A | 3 mm | 3 mm |
| Tuft Density | N/A | n/a | n/a |
| Pile Weight | TPA 1 ISO 9073 T.2 | 250 g/m2 | 250 g/m2 |
| Total mass | TPA 1 ISO 9073 T.1 | 850 g/m2 | 850 g/m2 |
| Primary Backing | ISO 13937-2-2001 | Latex | Latex |
| Pile Height | DIN 53351 | 2 mm | 2 mm |
| Width | TPA 1 ISO 9073 T.8 | 400/200/160/110/130 | 400/200/160/110/130 |
| Roll length | In production | 50/25 m1 | 50/25 m1 |
| Fastness to Light | ISO 105 B01 (1 tm 8) | < 5 | < 5 |
| Fire Resistance | DIN 4102 | norm Bfl / S1 | norm Bfl / S1 |

Printingcarpets.com [Bet you can print on it]