
ILFORD
ILFOJET
SOLVENT & LATEX MEDIA RANGE

Glossy Backlit Film

IJGTF6

Semi-matt translucent polyester film



FEATURES

Wipefast
High color brilliance
Water resistant
Scratch resistant

APPLICATION

Spot and transmitted light applications
Prints for lightboxes
Areas with a high humidity

PRINTER & INK COMPATIBILITY

This media is designed for use with most Latex-, ECO-Solvent-, Solvent- and UV- printer systems from major manufacturers.

IMPORTANT Printer and driver settings may need careful setup to ensure optimum performance. Ink loads need to be set appropriately for the ink/printer combination in use.

PHYSICAL PROPERTIES

Weight	200 gsm
Opacity	45 %
Caliper	150 µ

ENVIRONMENTAL CONDITIONS

Operating	15–25°C, 35–65% r.h. non-condensing
Storage	15–25°C, 35–65% r.h. non-condensing

ADDITIONAL INFORMATION

Finished prints should be interleaved and stored carefully to prevent scratching.
Fine art ink and print surfaces are more delicate than conventional RC inkjet prints and should be handled with care.

Note: Please include always the batch number to questions about the product or complaints. (see inside sleeve)

Specifications subject to change without notice.
All trademarks are the property of their respective companies.

AVAILABLE SIZES

(30")76,2 cm x 20 m
(36")91,4 cm x 20 m
(42")106,7 cm x 20 m
(50")127,0 cm x 20 m
(54")137,0 cm x 20 m
(60")152,4 cm x 20 m

SAMPLE ROLL

(36")91,4 cm x 10 m