

Verso195 195MSD**Double Side Printable Lightblock Polyester Film****Applications**

- Roll-up, displays, hanging banners
- Shop window display backdrop
- Glass (combined with mounting tape)

Benefits


- Double sided printable film, with backlight stop core
- Matt both sides
- 100% blockout even in strong sunlight, no show-through
- Dry off the printer for quick reversing
- No lamination necessary

Post Printing Information for Latex & Solvent Inks:

As with all filmic media, this product must be allowed to “gas-out” after printing.

This can be achieved by leaving the prints face up, ideally 24 hours, to set and harden the unique scratch resistant properties.

If unable to do this e.g. with a long print run, after printing the roll stand it vertically and loosely unwind as much as possible, to allow air in and gases out.

Printability:**Thickness:****Available widths:****Recommended Conditions:**

Printroom	15°C - 30°C	30% - 65% RH
Usage	-40°C - 80°C	10% - 90% RH
Storage	10°C - 20°C	20% - 50% RH



KERNOW COATINGS | Kernick Road | Penryn | Cornwall | TR10 9DQ | UK

www.kernowcoatings.com | sales@kernowcoatings.com | T: +44 (0)1326373147

Registered in England | No. 1092182 | A Member of the Sensitisers Group of Companies