



ELECTRICALLY CHARGED  
POLYPROPYLENE



ClingZ® is an adhesive-free electrically charged film that adheres to any dry interior surface and is effortless to reposition.

### ClingZ

- Ideal for temporary indoor marketing applications
- Effortless to apply, remove and reposition to any dry interior surface
- Adhesive free – no glue, tape, tacks or pins required
- Recyclable, chemically inert, PVC-Free and phthalate-free
- Can be die cut, kiss cut and plotter cut
- Available in white and clear
- Four grades engineered specifically for offset (ClingZ® Standard Offset and ClingZ® Versaliner), HP Indigo and UV wide format

**Print Compatibility:** Offset (Conventional and UV), HP Indigo and UV Wide Format\*

### Easy to apply and remove from these surfaces:



ClingZ is not to be confused with Static Cling Vinyl. Static Cling Vinyls cling to glass because of their high plasticizer content. **They do NOT cling by static.** Only ClingZ gets its cling properties due to having an embedded static charge.

### Applications

- Screen Safe Labels
- In-Store Promotional Signage
- Large Format Graphics
- Tileable Murals
- P.O.P. Signage
- Reverse Sided Graphics
- Trade Show & Event Signage
- Window Graphics
- Holiday Décor & Decals
- Guerrilla Marketing

Certified for  
HP Indigo



800.826.4886 | sales@nekoosa.com

NEKOOSA.COM | f @ in You Tube

07.28.21 | M1386



ELECTRICALLY CHARGED  
POLYPROPYLENE



## STOCKED PRODUCTS ▶

	Color	SKU #	Size	GSM	M Wgt	Qty/Unit
<b>ClingZ Standard Offset</b>						
White		71100	19" x 25"	240	162.2	2000/skid
		71101	23" x 35"		274.8	2000/skid
		71102	28" x 40"		382.4	2000/skid
		71105	19" x 25"		162.2	200/carton
		71106	23" x 35"		274.8	200/carton
		71107	28" x 40"		382.4	200/carton
	Clear		71110		19" x 25"	243
		71111	23" x 35"	278.3	2000/skid	
		71112	28" x 40"	387.2	2000/skid	
		71115	19" x 25"	164.2	200/carton	
		71116	23" x 35"	278.3	200/carton	
		71117	28" x 40"	387.2	200/carton	
<b>ClingZ Versaliner Offset*</b>						
White		71200	20" x 28"	243	193.6	2000/skid
		71201	28" x 40"		387.2	2000/skid
		71205	20" x 28"		193.6	250/carton
		71206	28" x 40"		387.2	250/carton
Clear		71210	20" x 28"	246	196.0	2000/skid
		71211	28" x 40"		392.0	2000/skid
		71215	20" x 28"		196.0	250/carton
		71216	28" x 40"		392.0	250/carton
<b>ClingZ HP Indigo</b>						
White		71300	12" x 18"	269	82.6	500/carton
		71301	13" x 19"		94.5	500/carton
		71310	20.5" x 19.5"		231.4	1200/skid
		71312	20.5" x 19.5"		231.4	300/carton
Clear		71305	12" x 18"	261	80.2	500/carton
		71306	13" x 19"		91.7	500/carton
		71311	20.5" x 19.5"		224.5	1200/skid
		71313	20.5" x 19.5"		224.5	300/carton
<b>ClingZ Wide Format</b>						
White		71501	42" x 150'	161	17	1/Roll
		71510	54" x 150'			1/Roll
Clear		71502	42" x 150'	155	22	1/Roll
		71511	54" x 150'			1/Roll

\*Select ClingZ Versaliner if extra finishing like die or kiss cutting is required.



ELECTRICALLY CHARGED  
POLYPROPYLENE

## TECHNICAL DATA ▶

Physical Properties			Offset	Versaliner	HP Indigo	UV Wide Format	
<b>Film</b>	Polypropylene	<b>Liner</b>	10 pt paper	10 pt paper	10 pt paper	PET	
<b>Color</b>	White and Clear	<b>Thickness</b>	Film	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)
			Liner	10 mil (254 μ)	10 mil (254 μ)	10 mil (254 μ)	3 mil (76.2 μ)
			Film + Liner	12 mil (304.8 μ)	12 mil (304.8 μ)	26 oz/in (286 n/m)	5 mil (127 μ)

Conditions for Use			Offset	Versaliner	HP Indigo	UV Wide Format
<b>Shelf Life</b>	1 year	<b>Application Time</b>	6 months	6 months	3 months	3 months
<b>Min. Application Temp.</b>	32° F (0° C)					
<b>Service Temp. Range</b>	0° F to 105° F (-17.8° C to 40.5° C)					
<b>Outdoor Durability</b>	None					

### General Printing and Designing Guidelines:

- Design for finished sizes of at least 3"x5" (8x12 cm).
- Convert PMS spot colors to CMYK process-ink builds.
- Stay within a total area coverage (TAC) of 220% in color build with a line screen of 150-175, and reduce screen values by using UCR or GCR.
- Avoid heavy deposits of ink near the edge to avoid curling.
- Right reading or reverse printing is possible.
- A 1" (2.5 cm) unprinted border will enhance the performance of the application.
- Add no more than 2 hits of opaque white before 4-color process when printing on clear film.
- Add white after the 4-color process if printing verse.
- This product is not suitable for screen printing or any type of coating, including varnishes or aqueous and UV coatings.

### Storing:

- Store in the original packaging at room temperature 65° F-80° F (18° C-27° C) with relative humidity of 25-50%.
- Acclimate the material to press room temperature for 24 hours prior to printing.
- Remove material from plastic bag right before the loading the press.
- Reseal unused materials in the original plastic bag.
- Paper liner is moisture sensitive and can curl if improperly stored.
- Unprinted ClingZ can be stored for up to one year.

### Additional Information:

- ClingZ is not to be confused with static cling vinyl. Static cling vinyls adhere to glass because of their high plasticizer content. They do not cling by static. Only ClingZ gets its cling properties due to having an embedded static charge.

<b>Certified for HP Indigo</b>	<b>HP CERTIFIED:</b> <b>ClingZ for HP Indigo Clear</b> 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900 <b>ClingZ for HP Indigo White</b> 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900
------------------------------------	--

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.