



ReMount™ Adhesive

Product Data Sheet

Updated : February 1997
Supersedes : February 1996

Product Description

3M ReMount™ is a non permanent adhesive that allows removal and repositioning many times without the need for respraying. It bonds lightweight paper, card and fabric securely to themselves and many smooth surfaces.

It is ideal for decorative stencilling, making collages, sticking posters to internal walls as well as many other creative applications.

The controlled spray action greatly reduces adhesive mist.

Physical Properties

Not for specification purposes

Solvent	Isohexane, Acetone
Flash Point	-46°C (propellant)
Propellant	Hydrocarbon
Contents	400 ml (254g)
Spray Pattern	Particle
Colour	Translucent/Clear
Shelf Life	12 months from date of receipt by customer when stored in the original carton at 21°C (70°F) & 50 % Relative Humidity

Additional Product Information

Does not contribute to ozone depletion.

Storage Conditions

Cool dry place. Best results are obtained when material is stored and applied at room temperature 16 to 27°C. Storage temperature must not exceed 49°C.

Directions for Use

Test before use on new applications.

Ensure all surfaces to be bonded are clean, dry and free from dust, oil and grease before application of adhesive.

Ensure that the nozzle points away from all persons and towards the surface to be sprayed. Turn the spray tip to select the desired spray width.

Shake can well before using, 5-10 seconds should be sufficient.

Hold the container 15 to 20 cms from the surface and apply evenly to cover the entire area.

To prevent nozzle from blocking, at the end of each day turn the can upside down and press the tip until spray is clear from adhesive, and wipe tip.

Clean Up:

Spray nozzle or excess adhesive may be cleaned with white spirits.

NOTE: When using solvents for clean up, it is essential that proper safety precautions are observed.

Health and Safety Information

For further information please contact our Product Responsibility / Toxicology Department in Bracknell on 01344 858000.

Values presented have been determined by standard test methods and are average values not to be used for specification purposes. Our recommendations on the use of our products are based on tests believed to be reliable but we would ask that you conduct your own tests to determine their suitability for your applications. This is because 3M cannot accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.

**Tapes & Adhesives Group**

3M United Kingdom PLC
3M House, PO Box 1,
Market Place,
Bracknell, Berkshire,
RG12 1JU

Product Information :

Tel 0870 60 800 50
Fax 0870 60 700 99

3M Ireland
3M House, Adelphi Centre,
Upper Georges Street,
Dun Laoghaire, Co. Dublin,
Ireland

© 3M United Kingdom PLC 2000

Customer Service :

Tel (01) 280 3555
Fax (01) 280 3509