Vertex Blackback Display Textile 240g/m2 FR B1

FEATURES AND BENEFITS

- Made of 100% warp-knitted polyester and has a white surface with a black resin coating on the back.
- This coating ensures complete opacity, making it suitable for backdrops applications.
- Its slight stretch feature makes it ideal for Frame and Pop-up materials.
- Compatible with a range of printing methods, including Dye-sub direct and Dye-sub transfer. It also works well with UV and Latex inks.

TECHNICAL SPECIFICATIONS

Properties	Test Method	Result
Total Weight	DIN EN ISO 2286-2,ASTM D 751	240gsm
Base Fabric	DIN 60001,ASTM D7641	100% Polyester
Shrinkage	190°C，1min	≤3%
Elasticity	Length*Width=200*50mm，Speed=100mm/min，Tension=20N	Warp: (3±1)%, Weft: (2±1)%
Flame Resistance	DIN 4102-1-B1, NFPA 701 Test1	DIN 4102-1-B1, NFPA 701 Test1
Recommend Fixation Temperature	N/A	190°C-210°C，1-2min
Calender Fixation Temperature	N/A	190°C-210°C，1-2min
Yellowing temperature	SUPRKC REX-C400, 30s	≥210°C

We operate a policy of continuous improvement and we reserve the right to alter products and specifications to reflect this without prior notice. Any information given either verbally or in writing is approximate only and given in good faith and does not constitute terms or part of any contract. We do not accept liability for variance including direct, indirect or consequential loss. The customer is deemed to have determined the suitability of the product for the use intended and assumes all associated risks and liabilities in connection with specifying, using or being unable to use any of the products.